



Facia mounted message display provides user information



Individual valve

A range of water treatment products designed to solve specific problems. Functioning as stand-alone units or as necessary pre treatment for Reverse Osmosis and Deionisation systems.

The FILTERMAT Control Module will initiate and control regenerations by time or by connecting to external switching devices. The control system used is also designed to connect to, and function with, Wychwood Water Systems Deionisation and Reverse Osmosis products providing automated water systems.

The FILTERMAT manifold is manufactured using individual quality valves. This enables precise control of service and regeneration sequences and effective media bed cleansing.

Products in Wychwood Water range:

IONMASTER RO

IONMASTER CO

IONMASTER CC

IONMASTER CCP

IONMASTER CLASSIC

FILTERMAT

SOFTENERS

NICON

Continuous Service and Technical Support

Wychwood Water Systems offer a full design and installation service.

All Wychwood products are covered by a one-year parts and labour warranty including a 24-hour technical Helpline facility.

A range of service contracts are available to provide continuous operational support and ensure your water system functions at optimum efficiency.

We also offer operator and maintenance staff training seminars for your own employees.

Wychwood Water Systems Ltd

Unit K, Country Park
Avenue Two, Station Lane
Witney, Oxon OX28 4YD

Tel: 01993 892211

Fax: 01993 892212

Email: sales@wychwood-water.com

Web: www.wychwood-water.com

THE FILTERMAT RANGE:

FILTERMAT OS

Dissolved organic matter originating from decaying vegetation and industrial solvents, are removed onto specially selected ion exchange resins.

FILTERMAT FE

Effectively removes dissolved iron and manganese from water supplies. Specially layered medias act as a catalyst and a filtration system to remove iron from the water and filter it out onto the media beds.

FILTERMAT AC

Uses a range of quality granular activated carbon to reduce organic matter, tastes, odours and free chlorine.

FILTERMAT ML

A multiple layer system adopted when more than one feed water problem exists.

A range of specialist medias are selected and layered, each to address a particular problem.

FILTERMAT units are manufactured in a range of sizes to provide a range of flow rates from 1m³ to 30m³ per hour.